



IC-A20

VHF

AIR BAND

TRANSCEIVER



OWNER'S MANUAL

FOREWORD

Thank you for choosing the **IC-A20 VHF AIR BAND TRANSCEIVER**. The **IC-A20** is designed with the latest computer technology and precision VHF engineering at ICOM, and has the following advanced features:

- VOR reception for navigation systems
- Weatherproof and dust-tight case with molded frame design
- 5W PEP (typical) output power
- 16 user-programmable memory channels
- 720 COM channels and 200 NAV channels

Please read this owner's manual carefully before using your **IC-A20** transceiver. With proper care, the **IC-A20** will provide years of dependable and enjoyable communication.

UNPACKING

Accessories	Qty.
① CM-7G BATTERY PACK	1
② CM-16U WALL CHARGER	1
③ Flexible antenna	1
④ Rainproof cap	1
⑤ DC power plug	1
⑥ Microphone plug	1
⑦ Earphone plug	1
⑧ Belt clip mounting screws	2
⑨ Belt clip mounting washers	2
⑩ IC-CM1 CIGARETTE LIGHTER CABLE	1
⑪ Belt clip	1
⑫ Earphone	1
⑬ Carrying case	1




TABLE OF CONTENTS

1. CONTROL FUNCTIONS.....	1 ~ 3	5. SCANNING OPERATION.....	15 ~ 18
TOP PANEL.....	1	OPERATING FULL SCAN.....	15
SIDE PANEL.....	2	OPERATING MEMORY SCAN.....	16
FRONT PANEL.....	2	OPERATING LOCKOUT SCAN.....	17
FUNCTION DISPLAY.....	3		
2. PRE-OPERATION	4 ~ 6	6. DUPLEX OPERATION	19 ~ 20
OPERATING CONNECTIONS.....	4	PROGRAMMING DUPLEX MODE.....	19
CHARGING CONNECTIONS.....	5	OPERATING DUPLEX MODE	20
BATTERY CHARGING	6		
3. BASIC OPERATION	7 ~ 12	7. VOR NAVIGATION	21 ~ 26
SETTING FREQUENCY.....	7	VOR INDICATORS.....	21
RECEIVING	9	FLYING TO A VOR STATION.....	23
TRANSMITTING	11	CROSSCHECKING POSITION.....	25
		VOR INDICATOR NOTE.....	25
4. MEMORY CHANNEL		8. OTHER FUNCTIONS	27 ~ 28
OPERATION	13 ~ 14	KEY LOCK FUNCTION.....	27
RECALLING A MEMORY CHANNEL.....	13	BEEP TONE FUNCTION	27
PROGRAMMING A MEMORY CHANNEL..	13	RESETTING MICROPROCESSOR	27
		9. OPTIONS	29 ~ 30
		10. SPECIFICATIONS	31

1. CONTROL FUNCTIONS

TOP PANEL

EXTERNAL DC POWER JACK (p. 4)

Connect the supplied IC-CM1 CIGARETTE LIGHTER CABLE or optional DM-2 DC-DC CONVERTER for mobile operation.


ANTENNA CONNECTOR

ANL SWITCH (p. 9)

Push this switch IN to reduce pulse-type noise.

RF OUTPUT POWER SWITCH (p. 11, 12)

OUT position : 5.0W PEP
IN position : 1.6W PEP



EXTERNAL MIC JACK (p. 4)

Connect an optional mic or headset to suit your operating preference.

EXTERNAL SPEAKER JACK (p. 4)


Connect either an external speaker or the supplied earphone for private listening.

VOLUME CONTROL and POWER SWITCH (p. 9)


SQUELCH CONTROL (p. 9, 10)

Set this control to the threshold point.


SIDE PANEL



FRONT PANEL




FUNCTION DISPLAY




2. PRE-OPERATION

OPERATING CONNECTIONS




CHARGING CONNECTIONS

• Removing the battery pack



Push the release button upwards, and slide the battery pack to the right to remove it from the transceiver.

*2 The CM-60A AC BATTERY CHARGER for multiple, simultaneous charging of up to six battery packs is also available.



BATTERY CHARGING

■ USING THE CM-16U WALL CHARGER

Prior to using the transceiver for the first time, the battery pack must be fully charged for optimum life and operation.

- 1) Connect the supplied CM-16U WALL CHARGER.
- 2) Charge the battery pack for about 15 hours.
 - The BATTERY CHARGE INDICATOR lights up while charging.
 - The battery pack need not be installed on the transceiver for charging. However, if it is, be sure to turn the transceiver OFF.

■ USING OTHER CHARGERS

CHARGER MODEL	CM-35	IC-CM1, DM-2
CHARGE TIME	1.5 hours	15 hours

■ BATTERY PACK NOTE

The full charge capacity of NiCd batteries may be reduced if repeatedly charged with only partial discharge periods. This is called the Battery Memory Effect. If the battery capacity seems lower than when new, discharge the battery pack completely through normal use, then charge fully using the proper charger.

■ BATTERY PACK CAUTIONS

- **NEVER** throw the battery pack into a fire since internal battery gas could cause an explosion.
- **NEVER** put the battery pack in water. If the battery pack is wet, be sure to wipe it dry.
- **NEVER** short the terminals on the top panel of the battery pack. Use the plastic insulator strip provided to prevent this.

3. BASIC OPERATION

SETTING FREQUENCY

■ RECALLING THE EMERGENCY FREQUENCY

(See EXAMPLE 1)

The IC-A20 can quickly recall the emergency frequency, 121.5MHz.

- 1) Turn power ON.
- 2) Push either the **FUNC** SWITCH on the side panel or **FE** KEY on the KEYBOARD.
- 3) Push the **0** KEY on the KEYBOARD.
 - "121.50" and "M" appear on the FUNCTION DISPLAY.
- 4) Push the **CLR** KEY to return to NORMAL MODE.

■ USING **▲** AND **▼** KEYS

(See EXAMPLE 2)

- 1) Turn power ON.
- 2) Push either the **▲** or **▼** KEY on the KEYBOARD to change the frequency by 25kHz steps.

■ USING NUMERICAL KEYS

(See EXAMPLE 3)

- 1) Turn power ON.
- 2) Push the desired numerical keys for setting the frequency then push the **ENT** KEY.
 - The frequency should be entered from the 10MHz digit.
 - The decimal point appears on the FUNCTION DISPLAY if the frequency is set completely.

EXAMPLE 1: Recalling the emergency frequency, 121.5MHz.

Push keys



Display

123.65

123.65^E

121.50_M

123.65

EXAMPLE 2: Changing frequency using the ▲ and ▼ keys.

Push keys



Display

123.65




123.675

123.65

123.625

EXAMPLE 3: Setting frequency for 118.20MHz using the numerical keys.

Push keys



Display


123.625

118

118.20

118.20

RECEIVING



1) Turn power ON.

2) Set the desired frequency.

3) Adjust [VOLUME] CONTROL.

4) Adjust [SQUELCH] CONTROL.

5) Push IN [ANL] SWITCH.

6) " **RX** " appears.

1) Turn the transceiver power ON.

2) Set the desired frequency. **(See page 7)**

- Receive frequency range: 108.000 ~ 135.975MHz

3) Adjust the [VOLUME] CONTROL to a suitable listening level.

4) Adjust the [SQUELCH] CONTROL until the speaker noise is quieted.

- " **RX** " disappears from the FUNCTION DISPLAY.

SQUELCH: If closed, the squelch mutes all noise from the speaker when no signal is received. This is useful while waiting for another station to call.

5) Push IN the AUTOMATIC NOISE LIMITER [ANL] SWITCH to reduce pulse-type noise such as that caused by engine ignition systems.

NOTE: The ANL function does not function in NAV BAND (108.000 ~ 117.975MHz) since VOR navigation errors could occur.

6) " **RX** " appears on the FUNCTION DISPLAY when the transceiver receives a signal.

TRANSMITTING

FLEXIBLE ANTENNA

CAUTION:

Transmitting without an antenna may damage the transceiver.

LIGHT SWITCH

Push this switch to turn ON and OFF the backlight for the FUNCTION DISPLAY.

PTT SWITCH

Push this switch to begin transmitting.

The **FUNC SWITCH** or **KEY** has a timer function and will turn OFF automatically unless another key is pushed.

RF OUTPUT POWER SWITCH


OUT position : 5.0W PEP
IN position : 1.6W PEP

FUNCTION SWITCH and KEY

Either the **FUNCTION SWITCH** or **KEY** can be used for operating secondary functions.

MICROPHONE

This microphone operates when the transceiver is transmitting. However, it will not operate if an external microphone is connected to the **EXTERNAL MICROPHONE JACK**.



NOTE: Listen carefully before transmitting to make sure your transmission will not interfere with any other communications.

See page 19 for duplex operation instructions using NAV BAND and COM BAND.

1) Set the desired frequency.

2) Select output power.

3) Push [PTT] SWITCH.

4) Release [PTT] SWITCH.

1) Set the desired frequency in COM BAND. **(See page 7)**

- Transmitting in NAV BAND is not permitted.
- COM BAND frequency range: 118.000 ~ 135.975MHz.

2) Select output power using the RF OUTPUT POWER SWITCH.

- **HIGH power** : Greater coverage for long distance transmissions.
- **LOW power** : Low output power conserving battery life.

3) Push the [PTT] SWITCH to begin transmitting. Speak into the microphone using your normal voice level.

- “TX” appears on the FUNCTION DISPLAY while transmitting.

4) Release the [PTT] SWITCH to return to receiving.

4. MEMORY CHANNEL OPERATION

RECALLING A MEMORY CHANNEL

- 1) Push **MR** KEY.
- 2) Enter a memory channel number.
- 3) Push **CLR** or **MR** KEY.

PROGRAMMING A MEMORY CHANNEL

- 1) Set NORMAL MODE.
- 2) Set the desired frequency.
- 3) Push **F** KEY then push **MR** KEY.
- 4) Push the desired memory channel number then push **ENT** KEY.

- 1) Push the **MR** KEY to select MEMORY CHANNEL MODE.
- 2) The following two methods are available to select the desired memory channel.
 - Push either the **▲** or **▼** KEY. Move through memory channels continuously by holding down either the **▲** or **▼** KEY.
 - Push keys for a desired memory channel number from 1 to 16 then push the **ENT** KEY. (See **EXAMPLE 5**)
- 3) Push the **CLR** or **MR** KEY to return to NORMAL MODE.

- 1) Set the NORMAL MODE. (See **EXAMPLE 4**)
- 2) Set the desired frequency using the **▲** or **▼** KEY or numerical keys. (See **page 7**)
- 3) Push the **F** KEY then push the **MR** KEY.
 - To cancel the programming memory channel, push the **F** KEY then push the **CLR** KEY.
- 4) Push keys for a desired memory channel number from 1 to 16 then push the **ENT** KEY.

EXAMPLE 4: Selecting the NORMAL MODE and MEMORY CHANNEL MODE.

Push keys

MR

MR or **CLR**

Display

118.20

124.65 M 1

118.20

EXAMPLE 5: Recalling memory channel 16 using the numerical keys.

Push keys

MR

1

6

ENT

MR or **CLR**

Display

124.65 M 1

124.65 M 16

124.65 M16

122.50 M16

118.20

EXAMPLE 6: Programming 118.20MHz in memory channel 16.

Push keys

(See frequency)

F

MR

1

6

ENT

Display

121.60

118.20

118.20^W 5

118.20^W 16

118.20

5. SCANNING OPERATION

The IC-A20 comes equipped with three scan functions, providing tremendous scanning versatility at the touch of just a few keys.

NOTE: Push the **[CLR]** KEY to indicate the course indicator when the scan stops on a VOR frequency while in MEMORY SCAN.

OPERATING FULL SCAN

- 1) Select NORMAL MODE.
- 2) Adjust [SQUELCH] CONTROL.
- 3) Push **[F]** KEY then Push **[▲]** or **[▼]** KEY.
- 4) Push **[CLR]** KEY.

SCAN TYPE	OPERATION
FULL SCAN	Scans full COM BAND frequency range 118 ~ 135.975MHz.
MEMORY SCAN	Scans all memory channels, 1 ~ 16.
LOCKOUT SCAN	Scans all memory channels while skipping locked out memory channels.

(See EXAMPLE 7)

- 1) Select NORMAL MODE. (See EXAMPLE 4)
- 2) Adjust the [SQUELCH] CONTROL to set the transceiver for scan operations.
 - “ **[RX]** ” disappears from the FUNCTION DISPLAY.
- 3) Push the **[F]** KEY then push either the **[▲]** or **[▼]** KEY to start the scan.
 - The decimal point blinks while in scanning operation.
 - The scan stops while receiving the signal. The scan resumes after the signal disappears.
- 4) Push the **[CLR]** KEY to cancel the scan.

OPERATING MEMORY SCAN

1) Push **[MR]** KEY.

2) Adjust [SQUELCH] CONTROL.

3) Push **[F]** KEY then push **[▲]** or **[▼]** KEY.

4) Push **[CLR]** KEY.

(See EXAMPLE 8)

1) Push the **[MR]** KEY to select MEMORY CHANNEL MODE.

2) Adjust the [SQUELCH] CONTROL to set the transceiver for scan operations.

- “**[RX]**” disappears from the FUNCTION DISPLAY.

3) Push the **[F]** KEY then push either the **[▲]** or **[▼]** KEY to start the scan.

- The decimal point blinks while in scanning operation.
- The scan stops while receiving the signal. The scan resumes after the signal disappears.


4) Push the **[CLR]** KEY to cancel the scan.

EXAMPLE 7: Operating FULL SCAN in an upwards direction.

Push keys



Display



OPERATING LOCKOUT SCAN

■ PROGRAMMING LOCKOUT CHANNEL

(See EXAMPLE 9)

- 1) Push **[MR]** KEY.
- 2) Select the desired memory channel.
- 3) Push **[F]** KEY then push **[9]** KEY.
- 4) Push **[CLR]** KEY.
- 1) Push the **[MR]** KEY to select MEMORY CHANNEL MODE.
- 2) Push keys for a memory channel you do not want to receive in while scanning then push the **[ENT]** KEY. (See page 13)
- 3) Push the **[F]** KEY then push the **[9]** KEY.
- 4) Push the **[CLR]** KEY to return to NORMAL MODE.

■ OPERATING LOCKOUT SCAN

(See EXAMPLE 10)

- 1) Push **[MR]** KEY.
- 2) Adjust [SQUELCH] CONTROL.
- 3) Push **[F]** KEY then push **[▲]** or **[▼]** KEY.
- 4) Push **[CLR]** KEY.
- 1) Push the **[MR]** KEY to select MEMORY CHANNEL MODE.
- 2) Adjust the [SQUELCH] CONTROL to set the transceiver for scan operations.
- 3) Push the **[F]** KEY then push either the **[▲]** or **[▼]** KEY to start the scan.
 - The decimal point blinks while in scanning operation.
 - The scan stops while receiving the signal. The scan resumes after the signal disappears.
- 4) Push the **[CLR]** KEY to cancel the scan.

EXAMPLE 8: Operating MEMORY SCAN in a downwards direction.

Push keys

MR

F

▲

Display

118.20

126.30 M 8

→

118.00 M 9▲

→

123.65 M10▲

...

132.80 M16▲

→

EXAMPLE 9: Programming the lockout channel on memory channel 8.

Push keys

MR

▲

F

9

CLR

Display

126.80

118.20 M 7

126.30 M 8

126.30 LOCK OUT M 8

126.30

EXAMPLE 10: Operating LOCKOUT SCAN in an upwards direction.

Push keys

MR

F

▲

(MEMO-10 skips)

Display

126.80

126.30 LOCK OUT M 8

→

118.00 M 9▲

→

123.65 LOCK OUT M10▲

...

132.80 M16▲

→

6. DUPLEX OPERATION

PROGRAMMING DUPLEX MODE

NOTE: To cancel the programming duplex mode, push the  KEY then push the  KEY.


- 1) Set a NAV frequency.
- 2) Push the  KEY then push the  KEY.
- 3) Set the desired transmit frequency on COM BAND then push the  KEY.
 - The transmit frequency is stored. (See **EXAMPLE 11**)
- 4) The duplex condition can be programmed in memory channels in which the NAV frequency is programmed. (See **EXAMPLE 12**)


EXAMPLE 11: Programming 121.20MHz for transmit frequency in DUPLEX MODE.


Push keys


      


Display













EXAMPLE 12: Programming the duplex condition in memory channel 16 in which 117.10MHz has already been programmed.


Push keys

Display







OPERATING DUPLEX MODE

- 1) Set a NAV or VOR frequency you want to receive in.
- 2) Push the **[F]** KEY then push the **[6]** KEY.
- 3) Push the [PTT] SWITCH to transmit.
 - **"TX"** appears and the displayed frequency is changed to the programmed transmit frequency.
- 4) Push the **[F]** KEY then push the **[6]** KEY again to turn DUPLEX MODE ON and OFF alternately. (See **EXAMPLE 14**)

EXAMPLE 13: Operating DUPLEX MODE on a NAV frequency of 117.10MHz and a transmit COM frequency of 121.20MHz.

Push keys

[F]

[5]

(Set frequency)

[ENT]

[F]

[6]

(Push PTT)

Display

[RX]
117.10
BEARING
214°
FROM

[RX] DUP-W
12180

[RX] DUP-W
12120

[RX] DUP
117.10
BEARING
214°
FROM

[TX] DUP
121.20

EXAMPLE 14: Turning DUPLEX MODE ON and OFF.

Push keys

[F]

[6]

[F]

[6]

Display


[RX] DUP
117.10
BEARING
214°
FROM

[RX]
117.10
BEARING
214°
FROM

[RX] DUP
117.10
BEARING
214°
FROM

7. VOR NAVIGATION

VOR INDICATORS



Ⓐ COURSE INDICATOR

Indicates where your aircraft is located on a VOR radial.

- **"OFF"** or **" - - - "** appear when your aircraft is too far from a VOR station or a frequency is not set correctly.

CAUTION: Measuring error of the course may occur by a maximum of 5°.

Ⓑ 2-DEGREE DEVIATION MARKS

Indicates course deviation by every 2 degrees.

Ⓒ COURSE DEVIATION NEEDLES

Indicates the deviation between the desired course and your actual flying course by every 2 degrees of deviation.

Ⓓ TO-FROM FLAG INDICATORS

Indicates whether the entered course is on line toward a VOR station or away from a VOR station.

Ⓔ OVERFLOW INDICATOR

Indicates if the deviation between the desired course and flying course is more than 10° degrees.

EXAMPLE 15: Changing the FLAG INDICATOR from **" TO "** to **" FROM "**, or vice versa.

Push keys

F

2

F

3

Display

RX
117.10
BEARING
214°
FROM

RX
117.10
BEARING
034°
TO

RX
117.10
BEARING
214°
FROM

FLYING TO A VOR STATION

1) Select a VOR station on your map.

2) Correct your aircraft heading.

3) Push **[E]** KEY then push **[4]** KEY.

4) Enter the desired course.

NOTE: To exit CDI MODE, access DVOR MODE and then access NORMAL MODE.

Example: Push the **[E]** KEY then push the **[4]** KEY.

5) Correct the desired course.

1) Select a VOR station on your map and set the frequency of the station.

- The COURSE INDICATOR indicates where you are located on a VOR radial from a VOR station.

2) Correct your aircraft heading using the COURSE INDICATOR number.

3) Push the **[E]** KEY then push the **[4]** KEY to indicate the COURSE DEVIATION INDICATOR (CDI).

4) Enter the desired course to the VOR station using numerical keys then push the **[ENT]** KEY.

- "▶▶▶▶▶" appears on the FUNCTION DISPLAY when your aircraft is off the desired course. (See Figure 2)
- The CDI indicates "OFF" when your aircraft is too far away from a VOR station, or the frequency is not set correctly at a VOR station.

5) When flying to a VOR station, or flying away from a VOR station, the CDI deviates to the right side of the display to show that the aircraft is off course to the left.

- To get back on course, turn your aircraft to the right until the CDI stops indicating deviation.

■ THE AIRCRAFT IS FLYING ON COURSE




Figure 1 The aircraft is flying on course

■ THE AIRCRAFT IS FLYING OFF COURSE




Figure 2 The aircraft is flying off course

CROSSCHECKING POSITION

1) Select two VOR stations on your map.

2) Set a frequency of one VOR station.

3) Set the other frequency of a VOR station.

4) Extend both the radials.

1) Select two VOR stations on your map.

2) Set a frequency of one VOR station.


- The COURSE INDICATOR lights up and indicates which VOR radial from the VOR station the aircraft is flying on. Note the number of the COURSE INDICATOR.

3) Set the other frequency of a VOR station.

- The COURSE INDICATOR lights up and indicates which VOR radial from the VOR station the aircraft is flying on. Note the number of the COURSE INDICATOR.

4) Extend the radials from each VOR station on your map. Your aircraft is located in the spot where both the lines cross each other. (See Figure 3)

VOR INDICATOR NOTE



"LOC" appears on the FUNCTION DISPLAY as shown at left when a localizer frequency is received by the IC-A20.

However, the FUNCTION DISPLAY does not indicate additional information about the localizer signal.

VORTAC
OLYMPIA
113.4 Ch 81 OLM

123.65
VORTAC
SEATTLE
116.8 Ch 115 SEA








Figure 3
Crosschecking position



EXAMPLE 16: Entering the desired course bearing 89° to a VOR station.

Push keys

F

2

F






4

8

9

ENT

Display



8. OTHER FUNCTIONS

KEY LOCK FUNCTION

This feature prevents accidental changes of the operating frequency or other functions selected from the KEYBOARD.

- 1) Push the  KEY then push the  KEY.
 - “KEY LOCK” appears on the FUNCTION DISPLAY.
- 2) To clear the KEY LOCK FUNCTION, push the  KEY then push the  KEY again.

BEEP TONE FUNCTION

The BEEP TONE FUNCTION provides beep sounds, allowing you to make sure of key entries each time a key is pushed.

- 1) Push the  KEY and then the  KEY to turn the function ON and OFF alternately.
- 2) The volume of the tone can be adjusted by turning the [VOLUME] CONTROL.

RESETTING MICROPROCESSOR

Reset the internal microprocessor:

- when the FUNCTION DISPLAY occasionally displays erroneous information during operation or when first applying power.
- when you want to erase all information in all memory channels.


Reset as follows:


Turn the power ON while pushing down both the  and  KEYS.



EXAMPLE 17: Operating with the KEY LOCK FUNCTION ON and OFF.


Push keys


Display

118.20


118.20


118.20
(KEY LOCK ON)



118.20



118.20
(KEY LOCK OFF)



EXAMPLE 18: Operating with the BEEP TONE FUNCTION ON and OFF.


Push keys


Display

118.20


118.20



118.20
(BEEP TONE ON)


118.20


118.20
(BEEP TONE OFF)


9. OPTIONS

**HS-10 + HS-10SA
HEADSET + VOX
UNIT**




- Headset with VOX (Voice Controlled) T/R switching.

**HS-10 + HS-10SB
HEADSET + PTT
SWITCH BOX**




- Headset with manual T/R switching.

**IC-CM9
SPEAKER-
MICROPHONE**




- Combination speaker and microphone.

**HS-20SB
PTT SWITCH BOX**




- Manual T/R switching unit for non-ICOM standard headset and mic.

**IC-CM1
CIGARETTE LIGHTER CABLE**




- For operation with a 12V-type external DC power source. (Same as the one supplied with the IC-A20.)

**DM-2
DC-DC CONVERTER**




- For operation with a 24V-type external DC power source.

**CM-35
AC BATTERY CHARGER**




- Charges the supplied battery pack in 1.5 hours.

**CP-10
BATTERY SEPARATION CABLE**




- Handy connector cable for separating the transceiver from the battery pack.

**CM-12G
BATTERY CASE**




- Output voltage : 15V
Battery : 10 AA size

HAND STRAP



- Handy hand strap for complete mobility.

SHOULDER STRAP



- For transporting your handheld transceiver.

**IC-MB16
MOBILE MOUNTING BRACKET**

- To place your IC-A20 in a convenient location.

**CM-7G
BATTERY PACK**

- An NiCd-type rechargeable battery pack. (Same as the one supplied with the IC-A20.)

10. SPECIFICATIONS

■ GENERAL

- Memory Channels : 16
- Channel Spacing : 25kHz
- Frequency Stability : 0.002% at $-10^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- Usable Temperature Range : $-10^{\circ}\text{C} \sim +50^{\circ}\text{C}$ ($+14^{\circ}\text{F} \sim +122^{\circ}\text{F}$)
- Dimensions : 65(74)mm(W) x 198(208)mm(H) x 35(42)mm(D)
Bracketed values include projections.
- Weight : 675g (including CM-7G BATTERY PACK and flexible antenna)
- Power Supply : 13.2V DC $\pm 15\%$ (for EXTERNAL DC POWER JACK)

■ RECEIVER

- Frequency Range : 108.000 ~ 135.975MHz
NAV BAND 108.000 ~ 117.975MHz
COM BAND 118.000 ~ 135.975MHz
- Sensitivity (with 50 Ω load) : NAV BAND 2 μV for 6dB S/N with 1kHz, 30% modulation
COM BAND 1 μV for 6dB S/N with 1kHz, 30% modulation
- Audio Output Power : 0.5W at 10% distortion
- Modulation Acceptance : A3E 6K00 (6A3)

■ TRANSMITTER

- Frequency Range : 118.000 ~ 135.975MHz
- Antenna Output Power : HIGH 5.0W PEP (1.5W carrier power)
(Typical) LOW 1.6W PEP (0.5W carrier power)
Power shows PEP with 85% modulation by a 1kHz audio tone.
- Emission Mode : A3E 6K00 (6A3)
- Modulation System : Low level modulation

• MEMO •

Please record the serial number of your **IC-A20** transceiver below for future servicing reference:

Serial number : _____

Date of purchase : _____

Place where purchased : _____



ICOM INCORPORATED

1-6-19, KAMIKURATSUKURI, HIRANO-KU,
OSAKA 547, JAPAN

A-0936 A
Printed in Japan